



**NozzTeq®**  
Taking Science to the Sewer®

866-620-5915

**SPINNING NOZZLES**

**NO REBUILDS OR OIL!**



## SPINNER™ SEWER NOZZLE

### EFFECTIVE GREASE REMOVAL

- No Oil, Rebuilds, bearings, expensive magnets or daily maintenance. Just wash it down at the end of the day and use it trouble free daily.
- HIGH QUALITY stainless steel and brass construction for maintenance free conditions and to minimize any breakdown while using in in corrosive sewer lines.
- Low jet with rear thrusting jets for maximum thrusting power.
- Has reversible body when you need to penetrate those stubborn blockages or use it as normal spinning sewer nozzle.
- NozzTeq Spinner is flexible and effective on removal of grease, smoother deposits, small roots etc.

**WHY Nozzteq? Because our Equipment is Engineered for Long Lasting Performance!**

**866-620-5915**

Nozzteq Inc. ADDRESS: 1949 Calumet Street - Clearwater, FL 33765

Phone: 1-866-620-5915 Fax: 1-603-413-6744

EMAIL: [info@nozzteq.com](mailto:info@nozzteq.com) HOME PAGE: [www.nozzteq.com](http://www.nozzteq.com)

866-620-5915

SPINNER™ SERIES



**PART NO. BLS**

**Spinner™ Specifications**

					
Model	BLS04	BLS06	BLS08	BLS12	BLS16
Hose Size	1/4"	3/8"	1/2"	1/2" up to 1 1/4"	1/2" up to 1 1/4"
Flow	3 - 10 US GPM	3 - 10 US GPM	10 - 50 US GPM	28 - 100 US GPM	50 - 265 US GPM
Pipe Size	2-6"	2-6"	3" up to 10"	6" and up	6" and up
Number. of Jets	4 Jets	4 Jets	4 Thrusters, 4+2 rot. jets	4 Thrusters, 4+2 rot. jets	6 Thrusters, 6+2 rot. jets
Jet Size	.4 up to 1.7 mm	.4 up to 1.7 mm	0.8 up to 2.8 mm	0.8 up to 2.8 mm	0.8 up to 6.0 mm
Weight	0.5 Lbs.	0.5 Lbs.	1.5 Lbs		115 Lbs.
Length	2.125"	2.125"	3.1"	4.3"	6.2"
Diameter	.75"	.75"	1.7"	2.5"	3.5"

**Variety of Sleds Available**



866-620-5915

Nozzteq Inc. ADDRESS: 1949 Calumet Street - Clearwater, FL 33765

Phone: 1-866-620-5915 Fax: 1-603-413-6744

EMAIL: info@nozzteq.com HOME PAGE: www.nozzteq.com